



	<b>NE2121Z</b>	<b>LBP</b>	<b>115 V</b>	<b>134a</b>
<b>Specifications</b> Approximate H. P. 1/4 Starting Torque High Refrigerant 134a Evaporator Temperature Low Evaporator Temperature -22° to 23°F			<b>Usage</b> Drinking Water Coolers Dehumidifiers Ice Machines Reach In Refrigerators Beer Coolers	

<b>LBP Performance</b>					
<b>Temperature °F</b>	-22	<b>-10</b>	5	14	23
<b>Capacity BTU/Hr</b>	634	<b>950</b>	1,484	1,882	2,338
<b>Power W</b>	213	<b>255</b>	314	353	396
<b>Current Amps</b>	3	<b>3.27</b>	3.7	4.01	4.37
<b>Temperature °C</b>	-30	<b>-23.3</b>	-15	-10	-5
<b>Capacity Kcal/Hr</b>	160	<b>239</b>	374	474	589

<b>LBP Rating</b>	<b>ASHRAE</b>	<b>Rating Point (Bolded above)</b>	<b>HBP Rating</b>	<b>ASHRAE</b>
Condensing	130°F		Condensing	130°F
Evaporator	-10°F		Evaporator	45°F
Return Gas	90°F		Return Gas	95°F
Ambient	90°F		Ambient	95°F
Liquid Temp.	90°F		Liquid Temp.	115°F

<b>Material</b>	<b>Part number</b>	<b>Description</b>	<b>Compressor Cross Ref.</b>	
Compressor	262BG70	NE2121Z	Model	Appl.
Relay	2283001	9660C-3027-182;MTRPH-63-08		
Overload	2321018	MRA6981-3261;TO808/G9		
Start Cap	2252230	145-174 mfd / 250V		
Grommet	2221003			
Sleeve	2222015			

**EMBRACO NORTH AMERICA, INC.**  
2800 Vista Ridge Dr. Suite 100, Suwanee Ga, 30024 Phone: 678-804-1337